

## Headquarter

**Taiwan : Thermaltake Technology Co.,Ltd.**  
Address: 8F, No.27, Lane 155, Sec.3, Pei Shen Road, Saen  
Keng Hsiang, Taipei Hsiang, Taiwan  
TEL: +886-2-2662-6501 FAX: +886-2-2662-6510  
E-mail: thermaltake@thermaltake.com

## Overseas Branch

**USA: Thermaltake Technology Inc.**  
Address: 525Parrittott Place, City of Industry, CA 91746  
TEL: +1-626-968-9189 FAX: +1-626-968-7659  
E-mail: davidh@thermaltake.com

## Europe:

**Thermaltake Europe B.V.**  
Address: Fortunaweg 15, 3113AN, Schiedam, Netherlands  
TEL: +31-10-409-0150 FAX: +31-10-409-0159  
E-mail: tt.europe@thermaltake.com

## Thermaltake Germany GmbH

Address: Oststrasse 26, 22844 Norderstedt, Germany  
TEL: +49(0)40/30-85-86-0 FAX: +49(0)40/30-85-86-89  
E-mail: info@thermaltake.de

## China: Thermaltake Beijing Co.Ltd

Address: #907, HaiTai Plaza, No.229, North 4th  
Ring Road, Haidian District, Beijing 100083 PRChina  
TEL: +86-10-8288-3703 FAX: +86-10-8288-3302  
E-mail: allen.hu@thermaltake.com

## Australia: Thermaltake Australia and New Zealand Pty Ltd

Address: Unit 1, 49 Henderson Road Rowville  
Victoria 3178 Australia  
TEL: +61-(03) 9763 1622 FAX: +61-(03) 9763 1677  
E-mail: sales@thermaltake.com.au  
URL: www.thermaltake.com.au

## Japan: Thermaltake Japan Inc.

Address: 2F, 1-8-19 Toyotaminami, Nerima-ku,  
Tokyo, 176-0014, Japan  
TEL: +81-3-3948-5616 FAX: +81-3-3948-5617  
E-mail: sales-jp@thermaltake.com



© 2005 Thermaltake Technology Co.,Ltd. All Rights Reserved.

DM131 2005.5

All other registered trademarks belong to their respective companies.

[www.thermaltake.com](http://www.thermaltake.com)


**VB5000**

*the Aluminum Extrusion Case with Liquid Cooling System*

**Tai-Chi**  
Thermaltake



**Tt Thermaltake**  
COOL ALL YOUR LIFE



**the Next Generation PC .....**



**T**ai Chi features a stylish and long-lasting aluminum body with bottom wheel stands with brakes. The front and side panel shines a radiant effect with electric blue LED fans. Upon opening the front hydraulic doors, the Tai Chi houses eleven interchangeable drive bays for maximum expandability, front-mounted USB 2.0 ports and audio jacks permits simple multimedia device connections, extra large thumb screws for easy opening of the side panel and two 120mm fans in the front and rear of the case for maximum cooling performance. With optimized internal space and fine quality airflow, the Tai Chi is also a better choice for building a liquid cooling system.

Tai Chi also highlights a horde of premium installation refinements with a removable aluminum motherboard tray with optional BTX upgradeable kit for upgrading and advancing users' computer systems, quick and easy installation for 5.25" drive bay devices and screw-less slots for easy assembling. It supports all motherboards up to ATX and is upgradeable to BTX using the optional BTX Upgradeable Kit.




**Liquid cooling system application:**

- Retaining holes for liquid cooling kits
- Optimize internal space for installing liquid cooling system



**Air cooling system application:**

- Optimized its air flow
- Minimized Noise Level





<b>Model</b>	Tai-Chi --- VB5001SNA (with liquid cooling system)
<b>Case Type</b>	Super Tower
<b>Net Weight</b>	19.7 Kg
<b>Dimension</b>	600 x 263 x 546 mm (H*W*D)
<b>Drive Bays</b>	11
<b>-Front Accessible</b>	Up to 10 x 5.25" , 1 x 3.5"
<b>-Internal</b>	3 x 3.5"
<b>Material</b>	Aluminum Extrusion
<b>color</b>	Silver & Black
<b>Expansion Slots</b>	7
<b>Motherboards</b>	Micro ATX, ATX, Extend ATX, BTX, Micro BTX, Pico BTX
<b>BTX upgraded kits</b>	SRM / Rear plate (option)

**Liquid Cooling system application**

- Liquid Cooling system**
- 4 in 1 universal waterblock: All copper base with blue LED, and universal clips
  - Cooling system: Dual 1300rpm 12 cm fan with performance radiator
  - 12V liquid pump: Powerful DC 12V liquid pump (84 L /Hour)
  - Liquid Tank: Easy to refill the coolant
  - Water tubes: Transparent green water pipes

- Case fan**
- Front (intake) : 120 x 120 x25 mm blue LED fan, 1300rpm, 17dBA,
  - Rear (Exhaust) : 120 x 120 x25 mm blue LED fan, 1300rpm 17dBA.

**Features**

- All aluminum extrusion built chassis
- Compact and stylish chassis
- BTX & ATX compatible
- Better choice for upgrading liquid cooling system
- Hydraulic side panel opening
- Tool-free installation
- Optimize internal space and airflow
- Support to 11 5.25" drive bays
- Relocate-able front control panel (Power, Reset switch, HDD & PWR LEDs)
- Removable aluminum motherboard tray
- Easy Lifting Handles


# -- Taichi with liquid cooling system overview --



**Refill liquid tank:**  
Easy to refill the coolant



**Water tube:**  
Transparent green pipes



## Cooling system:

- Dual 1300 rpm, 12 x 12 x 2.5 cm fans, 17 dBA.
- Performance radiator dimension: H 27 x W 22 x D 3.3 cm



## Waterblock:

- All copper base with blue LED acrylic cover.
- Apply to Intel LGA775 / 478, AMD K8 / K7, enclosed universal clips.

## Powerful pump:

- DC 12V liquid pump.
- Flow rate: 84 L / hr

## ATX / BTX

- fits Intel Extend ATX (12" x13" ),  
ATX(12" x9.6" ), micro ATX  
(9.6" x9.6" )
- fits Intel BTX (10.5" x12.8" ),  
micro BTX(10.5" x10.4" ),  
pico BTX(10.5" x8" )

**BTX upgraded kit (option)**  
P/N : A9449



BTX SRM



BTX rear plate




**BTX**

ATX / BTX platform compatibility



**ATX**



<b>Model</b>	Tai-Chi --- VB5000SNA
<b>Case Type</b>	Super Tower
<b>Net Weight</b>	17.1 Kg
<b>Dimension</b>	600 x 263 x 546 mm (H*W*D)
<b>Cooling System</b>	<ul style="list-style-type: none"> <li>•Front (intake) : 120 x 120 x25 mm blue LED fan, 1300rpm, 17dBa,</li> <li>•Rear (Exhaust) : 120 x 120 x25 mm blue LED fan, 1300rpm 17dBa.</li> </ul>
<b>Drive Bays</b>	11
<b>-Front Accessible</b>	Up to 10 x 5.25" , 1 x 3.5"
<b>-Internal</b>	3 x 3.5"
<b>Material</b>	Aluminum Extrusion
<b>color</b>	Silver & Black
<b>Expansion Slots</b>	7
<b>Motherboards</b>	Micro ATX, ATX, Extend ATX, BTX, Micro BTX, Pico BTX
<b>BTX upgraded kits</b>	SRM / Rear plate (option)

- Features**
- All aluminum extrusion built chassis
  - Compact and stylish chassis
  - BTX & ATX compatible
  - Better choice for upgrading liquid cooling system
  - Hydraulic side panel opening
  - Tool-free installation
  - Optimize internal space and airflow
  - Support to 11 5.25" drive bays
  - Relocate-able front control panel (Power, Reset switch, HDD & PWR LEDs)
  - Removable aluminum motherboard tray
  - Easy Lifting Handles

# Inside Structure



front view

Drive Bays

11

Front Accessible

Up to 10 x 5.25", 1 x 3.5"

Internal

3 x 3.5"

Dimension (H\*W\*D)

600 x 263 x 546 mm



Side Panel



Front view



Rear view (ATX)



Rear view (BTX)



## Features



- 1 Extra large thumb screws for easy opening side panel



- 2 Wheels stands with brake



- 3 Built-in 5.25" drive bay accessory box



- 4 3 x 3.5" HDD module with 12 cm blue LED fan



- 5 Dual USB 2.0, IEEE 1394 Firewire, Audio & Speaker ports



- 6 Screwless slots for easy assembling



- 7 Removable mother board tray



- 8 Tool-free installation for 5.25" device



- 9 Hydraulic opening



- 10 Ventilation opening on foundation of chassis



- 11 Front opening for air flow