

SHARK



www.thermaltake.com

Headquarter

Taiwan : Thermaltake Technology Co.,Ltd.
Address: 8F, No.27, Lane 155, Sec.3, Pei Shen Road, Saen Keng Hsiang, Taipei Hsiang, Taiwan
TEL:(886) 2-2662-6501 FAX:(886) 2-2662-6510
E-mail: thermaltake@thermaltake.com

Overseas Branch

USA: Thermaltake Technology Inc.

Address: 525Parritott Place,
City of Industry, CA 91746
TEL: (626)968-9189 FAX: (626)968-7659
E-mail: davidh@thermaltake.com

France: Thermaltake France

Address: 73, Bid de Courcerin Parc du Courcerin 77185 Lognes
TEL: + 33 - (0)160 1763 15 FAX: + 33 - (0)1 60 17 63 16
E-mail : albertl@thermaltake.com

China: Thermaltake Beijing Co.Ltd

Address: #907,HaiTai Plaza, No.229, North 4th Ring Road, Haidian District, Beijing 100083 PRChina
TEL:+86-10-82883159/3189 FAX:+86-10-82376577
E-mail: allen.hu@thermaltake.com

Australia: Thermaltake Australia and New Zealand Pty Ltd

Address: Unit 1, 49 Henderson Road Rowville Victoria 3178 Australia
TEL: +61- (03) 9763 1622 FAX: +61- (03) 9763 1677
E-mail: sales@thermaltake.com.au
URL: www.thermaltake.com.au

Japan: Thermaltake Japan Inc.

Address: No.5-A, Hei-An Bldg 2-6-16 Okubo, Shinjuku-ku, Tokyo, 169-0072, Japan
TEL: +81- 3-3203-3371 FAX: +81- 3-3203-3372
E-mail: sales-jp@thermaltake.com

Full Tower

Aluminum Case



SHARK

Full Tower Aluminum Case

SHARK
SHARK VA7000 SERIES
Full Tower Aluminum Case



Compatible with liquid cooling



Audio & Speaker



Shark-style panel



IEEE 1394



USB 2.0



LED Fan



120x120mm x2
12025 Fan



Removable M/B tray



6.8kg Weight
Ultra Light

Model	VA7000SWA	VA7000BWA
Case Type	Full Tower	
Side Panel	Honeycomb See through side panel	
Net Weight	6.8 kg	
Dimension (H*W*D)	540 x 205 x 500 mm	
Cooling System	Front	120 x 120 x 25 mm fan, 2000rpm, 21dBA (intake)
	Rear	120 x 120 x 25 mm blue LED fan , 2000rpm, 21dBA (exhaust)
Drive Bays	12 External: 5 x 5.25" , 2 x 3.5" Internal: 5 x 3.5"	
Material	Chassis : 1.0 mm Aluminum Front Door: Aluminum	
color	Silver	Black
Expansion Slots	7	
Motherboards	Removable M/B tray fits Micro ATX & Standard ATX	
Thermal Test	Tambient : 38 °C , Intel thermal requirement validated	
USB & 1394Firewire	Dual USB2.0, IEEE1394 Firewire , audio & speaker ports	
Features	<ul style="list-style-type: none"> ➤Removable motherboard tray ➤Dual 12 cm fans in front & rear ➤FitsTt liquid cooling system (performance radiator with 12 cm fan) or other specific brands. ➤See - through side panel with EMI shield. ➤Security lock in front bezel and side panel. ➤Retractable foot stand 	



Thermaltake
COOL ALL YOUR LIFE

© 2004 Thermaltake Technology Co.,Ltd. All Rights Reserved.
DM095 REV.B 2004.9

All other registered trademarks belong to their respective companies.

Thermaltake
COOL ALL YOUR LIFE

SHARK


Full Tower Aluminum Case

SHARK VA7000 SWA

Full Tower Aluminum Case



Honeycomb see-through side panel with EMI shield. Opening ratio 61%. (M/B & CPU cooler are not included)



Front View Side View

Chassis overview

SHARK

Full Tower Aluminum Case

SHARK VA7000 BWA

Full Tower Aluminum Case



Honeycomb see-through side panel with EMI shield. Opening ratio 61%. (M/B & CPU cooler are not included)



Front View Side View

Chassis overview

Compatible with liquid cooling system >>>



Fits all Tt liquid cooling system (performance radiator with 12 cm fan) or other specific brands.

(Option: Watercooling system)




Recommendation: Thermaltake Bigwater (P/N: CL-W0005) liquid cooling system




Detail Features >>>



1 Dual USB 2.0, IEEE1394 Firewire, audio & speaker ports
2 Screwless add-on card clip
3 Thumb screws
4 Security lock in front bezel and side panel.



5 Retractable foot stand
6 Honeycomb see-through side panel with EMI shield. Opening ratio 61%.
7 Disk shockproof pads with EMI grounding
8 Removable motherboard tray (M/B is not included)



9 Sliding drive rail assembly
10
11



12 2-way open

Drive Bay:

- External: 5.25" x 5, 3.5" x 2
- Internal: 3.5" x 5



Best Ventilation: 12cm fans in front & rear

Dual 12cm cooling fans



Inside Structure